

# Overview (1A)

---

Copyright (c) 2009 Young W. Lim.

Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.2 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License".

Please send corrections (or suggestions) to [youngwlim@hotmail.com](mailto:youngwlim@hotmail.com).

This document was produced by using OpenOffice.

# Calculating the Mean

*The mean of 3 numbers*

$$m = \frac{a + b + c}{3}$$

$$\frac{40 + 50 + 60}{3} = 50 \quad \text{Integer number}$$

$$\frac{45 + 53 + 63}{3} = \frac{161}{3} = 53.6666666... \quad \text{Real number}$$

# Calculating the Mean - in C

```
int      a, b, c;  
int      mean;
```

```
a = 40;  
b = 50;  
c = 60;
```

```
mean = (a + b +c) / 3;
```


```
int      a, b, c;  
float    mean;
```

```
a = 45;  
b = 53;  
c = 63;
```

```
mean = (a + b +c) / 3.0;
```


- \* Variable
- \* Type
- \* Assignment
- \* Operator

# Variable - Int



int type

# Variable - Float




# Memory and & operator

a	40
b	50
c	60
mean	50

**a = 40;**

*where:* address of a  
*what:* data 40




# Memory and Pointer

a	40
b	50
c	60
mean	50

a\_ptr = &a;

where: addr of a\_ptr  
what: data &a  
(addr of a)




# Memory and \* operator

a	40
b	50
c	60
mean	50

`*a_ptr = 55;`

where: data of a\_ptr  
    (→ another addr )  
what: data 55



# Pointer Type

```
int a;
```

a holds data

&a

value of a

```
int *a_ptr;
```

a\_ptr holds address  
\*a\_ptr holds data

&a\_ptr

value of a\_ptr  
(→ an address)

value of a\_ptr

\*a\_ptr

# Printf Function

---

## Expected Output

*The mean of three numbers*

*a = 40*

*b = 50*

*c = 60*

*mean(40, 50, 60) => 50*

```
printf("The mean of three numbers \n");
printf("a = %d \n", a);
printf("b = %d \n", b);
printf("c = %d \n", c);
printf("mean (%d, %d, %d) => %d \n", a, b, c, mean);
```

# Main Function (1)

---

```
main (void)
{
    int      a, b, c;
    int      mean;

    a = 40;
    b = 50;
    c = 60;

    mean = (a + b + c) / 3;

    printf("The mean of three numbers \n");
    printf("a = %d \n", a);
    printf("b = %d \n", b);
    printf("c = %d \n", c);
    printf("mean (%d, %d, %d) => %d \n", a, b, c, mean);

}
```

# Scanf Function


## Expected Input

Enter three numbers!

a = 40 ↵

b = 50 ↵

c = 60 ↵



```
printf("Enter three numbers! \n");
printf("a = "); scanf("%d", &a);
printf("b = "); scanf("%d", &b);
printf("c = ");   scanf("%d", &c);
```

# Main Function (2)

```
main (void)
```

```
{
```

```
    int      a, b, c;
```

```
    int      mean;
```

```
    printf("Enter three numbers! \n");
```

```
    printf("a = "); scanf("%d", &a);
```

```
    printf("b = "); scanf("%d", &b);
```

```
    printf("c = ");     scanf("%d", &c);
```

```
    mean = (a + b + c) / 3;
```

```
    printf("The mean of three numbers \n");
```

```
    printf("a = %d \n b = %d \n c = %d \n", a, b, c);
```

```
    printf("mean (%d, %d, %d) => %d \n",
           a,      b,      c,      mean );
```

```
}
```

# Main Function (2)

```
main (void)
{
    int      a, b, c;
    int      mean;

    enter_numbers( ? );

    compute_mean( ? );

    print_numbers( ? );

}
```

# Compute\_mean Function

```
float compute_mean (int x, int y, int z)
{
    int     avg;

    avg = (x + y + z) / 3.0;

    return( avg );

}

main (void)
{
    int     mean;

    mean = compute_mean(40, 50, 60);

}
```

\* Call by Value  
\* Return Value  
\* Local Variable

# Enter\_numbers Function

```
void enter_numbers (int *x, int *y, int *z)
{
    printf("Enter three numbers! \n");
    printf("a = "); scanf("%d", x);
    printf("b = "); scanf("%d", y);
    printf("c = ");   scanf("%d", z);
}
```

```
main (void)
{
    int     a, b, c;

    enter_numbers(&a, &b, &c);

}
```

\* Call by Reference  
\* No Return Value

# Print\_numbers Function

```
void print_numbers (int x, int y, int z, float avg)
{
    printf("The mean of three numbers \n");
    printf("a = %d \n b = %d \n c = %d \n", x, y, z);
    printf("mean (%d, %d, %d) => %d \n",
           x, y, z, avg );
}
```

```
main (void)
{
    int     a, b, c;
    float   mean;

    print_numbers(a, b, c, mean);

}
```

\* Call by Value  
\* Return Value

# Main Function (3)

---

```
void enter_numbers (int *x, int *y, int *z);
float compute_mean (int x, int y, int z);
void print_numbers (int x, int y, int z, float avg);
```

```
main (void)
{
    int      a, b, c;
    int      mean;

    enter_numbers(&a, &b, &c);

    mean = compute_mean(a, b, c);

    print_numbers(a, b, c, mean);
}
```

## References

- [1] Essential C, Nick Parlante
- [2] Efficient C Programming, Mark A. Weiss
- [3] C A Reference Manual, Samuel P. Harbison & Guy L. Steele Jr.
- [4] C Language Express, I. K. Chun