

CT Convolution (1A)

•




Copyright (c) 2010 - 2014 Young W. Lim.

Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.2 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License".





Please send corrections (or suggestions) to youngwlim@hotmail.com.

This document was produced by using OpenOffice and Octave.

Convolution: delayed response of $h(t)$ (1)












delayed response
by 1






Convolution: delayed response of $h(t)$

(2)




Convolution: delayed response of $h(t)$

(3)






$\delta(t-v) \rightarrow h(t-v)$
 $x(v) \delta(t-v) \rightarrow x(v) h(t-v)$


input value at time v
 $\rightarrow x(v)$
 delayed impulse response
 $\rightarrow x(v) h(t - v)$



$$x(t) = \int x(v)\delta(t-v) dv$$




Convolution: Commutative Law




$$x(v) \xrightarrow{\text{Flip}} h(v) \xrightarrow{\text{Shift}} h(-v) \xrightarrow{\text{Shift}} h(t-v)$$
$$\int x(v)h(t-v) dv = y(t)$$

$$\int h(v)x(t-v) dv = y(t)$$

$$h(v) \xrightarrow{\text{Shift}} x(v) \xrightarrow{\text{Flip}} x(-v) \xrightarrow{\text{Shift}} x(t-v)$$




Convolution: delayed response of $x(t)$ (1)






Convolution: delayed response of $x(t)$

(2)




Convolution: delayed response of $x(t)$

(3)






$\delta(t-v) \rightarrow x(t-v)$
 $h(v) \delta(t-v) \rightarrow h(v)x(t-v)$


input value at time v
 $\rightarrow h(v)$
 delayed impulse response
 $\rightarrow h(v)x(t-v)$




$$h(t) = \int h(v)\delta(t-v) dv$$






FIR and IIR









Impulse Response






delayed response
by 0.5



delayed response
by 1




LTI System








$x(t) = \delta(t-t_1+1) + \delta(t-t_1+.5) + \delta(t-t_1)$

$y(t) = h(t-t_1+1) + h(t-t_1+.5) + h(t-t_1)$


Computing $y(t_1)$: Output at $t = t_1$



$$x(t) = \delta(t-t_1+1) + \delta(t-t_1+.5) + \delta(t-t_1)$$




Computing $y(t_1)$: delayed impulse response $h(t)$




$$x(t) = \delta(t-t_1+1) + \delta(t-t_1+.5) + \delta(t-t_1)$$


delayed impulse response – $h(t)$



$$y(t_1) = h(1) + h(.5) + h(0)$$



$$x(t) = \delta(t-t_1+1) + \delta(t-t_1+.5) + \delta(t-t_1)$$



$$y(t) = h(t-t_1+1) + h(t-t_1+.5) + h(t-t_1)$$

Computing $y(t_1)$: flip and shift $x(t)$

$$x(t) = \delta(t-t_1+1) + \delta(t-t_1+.5) + \delta(t-t_1)$$

↓ Change of variables $t \rightarrow v$

$$x(v) = \delta(v-t_1+1) + \delta(v-t_1+.5) + \delta(v-t_1)$$

↓ Flip around y axis and then shift to the right by t $v \rightarrow t-v$

$$x(t-v) = \delta(t-v-t_1+1) + \delta(t-v-t_1+.5) + \delta(t-v-t_1)$$

$$y(t) = \int x(t-v) h(v) dv$$

$$= \int \underbrace{\delta(t-v-t_1+1)}_{\text{impulse response delayed by } t_1-1} h(v) dv \rightarrow h(t-t_1+1)$$

$$+ \int \underbrace{\delta(t-v-t_1+.5)}_{\text{impulse response delayed by } t_1-.5} h(v) dv \rightarrow h(t-t_1+.5)$$

$$+ \int \underbrace{\delta(t-v-t_1)}_{\text{impulse response delayed by } t_1} h(v) dv \rightarrow h(t-t_1)$$

$$y(t) = h(t-t_1+1) + h(t-t_1+.5) + h(t-t_1)$$

→ $y(t_1) = h(1) + h(.5) + h(0)$

Computing $y(t_1)$: flip and shift $h(t)$

$h(t)$



Change of variables

$$t \rightarrow v$$

$h(v)$



Flip around y axis and then shift to the right by t

$$v \rightarrow t-v$$

$h(t-v)$

$$y(t) = \int x(v)h(t-v) dv$$

$$= \int \delta(v-t_1+1)h(t-v) dv \rightarrow h(t-t_1+1) \text{ impulse response delayed by } t_1-1$$

$$+ \int \delta(v-t_1+.5)h(t-v) dv \rightarrow h(t-t_1+.5) \text{ impulse response delayed by } t_1-.5$$

$$+ \int \delta(v-t_1)h(t-v) dv \rightarrow h(t-t_1) \text{ impulse response delayed by } t_1$$

$$y(t) = h(t-t_1+1) + h(t-t_1+.5) + h(t-t_1)$$

$$\Rightarrow y(t_1) = h(1) + h(.5) + h(0)$$

Computing $y(t_1)$: commutativity (1)

$$y(t) = \int x(v)h(t-v) dv$$

$$= \int \delta(v-t_1+1)h(t-v) dv$$

$$+ \int \delta(v-t_1+.5)h(t-v) dv$$

$$+ \int \delta(v-t_1)h(t-v) dv$$

$$\Rightarrow h(t-t_1+1)$$

$$\Rightarrow h(t-t_1+.5)$$

$$\Rightarrow h(t-t_1)$$



$$y(t) = \int x(t-v)h(v) dv$$

$$= \int \delta(t-v-t_1+1)h(v) dv$$

$$+ \int \delta(t-v-t_1+.5)h(v) dv$$

$$+ \int \delta(t-v-t_1)h(v) dv$$

Flip and Shift $h(t)$



Computing $y(t_1)$: commutativity (2)

$$y(t) = \int x(v)h(t-v) dv$$

$$= \int \delta(v-t_1+1)h(t-v) dv$$

$$+ \int \delta(v-t_1+.5)h(t-v) dv$$

$$+ \int \delta(v-t_1)h(t-v) dv$$

$$\Rightarrow h(t-t_1+1)$$

$$\Rightarrow h(t-t_1+.5)$$

$$\Rightarrow h(t-t_1)$$



$$y(t) = \int x(t-v)h(v) dv$$

$$= \int \delta(t-v-t_1+1)h(v) dv$$


$$+ \int \delta(t-v-t_1+.5)h(v) dv$$

$$+ \int \delta(t-v-t_1)h(v) dv$$


Flip and shift input $x(t)$




Computing $y(t_1)$: commutativity (3)



Computing $y(1)$, $y(t)$




Computing $y(1)$: shift & flip $x(t)$




delayed impulse
response at $t=1$

$$x(0)h(1)$$




delayed impulse
response at $t=1$

$$x(.5)h(.5)$$



delayed impulse
response at $t=1$


$$x(1)h(0)$$




$x(1 - v) h(v)$

$y(t)$

$$x(0)h(1)$$









$$x(.5)h(.5)$$




$$x(1)h(0)$$


Computing $y(t)$: shift & flip $x(t)$




Computing $y(t)$: the earliest and latest inputs




Computing $y(t)$, $y(s)$



Computing $y(t)$: earliest and latest inputs




$$y(t) = \int x(t-v)h(v) dv$$



this value of $h(t)$
is used first


Computing $y(t)$: delayed impulse response




these inputs affects
the output value at t

delayed impulse response

the latest
input value
that affects the output value $y(t)$



Computing $y(t)$: multiplication sequence



References

- [1] <http://en.wikipedia.org/>
- [2] J.H. McClellan, et al., *Signal Processing First*, Pearson Prentice Hall, 2003